

DOWNLIGHT SERIES

Ultra-Slim Flat Canless Downlight J-box included

Color Changeable 2700K/3000K/3500K/4000K/5000K

Type:

Fixture:

TECHNICAL DATA

PRODUCT	DRF-305	DRF-406	DRF-609	DRF-815
SIZE	3"	4"	6"	8"
WATTAGE	8W	10W	12W	18W
LUMENS	500 LM	650 LM	900 LM	1500 LM
EFFICACY	62.5 LM/W	65 LM/W	75 LM/W	83 LM/W
CC	2700K/ 3000K/ 3500K/ 4000K/ 5000K Color Changeable			
VOLTAGE	120V			
DIMMING	TRIAC			
CRI	>90			
BEAM ANGLE	110°			
POWER FACTOR	0.9			
WORKING TEMP.	-5°F ~ 104°F			



DESCRIPTION

The Color Changeable Ultra-Slim Flat Canless Downlight brings you a modern & unique lighting solution. The Canless Ultra-Slim design reduce the required of clearance for the installation. Also they are good for Indoor/Outdoor locations and dont require can housing for the installation anymore. Allows you to install them in where a recessed can wont fit, simplified installation in drywall or suspended ceilings eliminates recessed can saving time and money. With 5 color selectable feature, this downlight satisfies most application needs in a shopping center, business buildings, hotels, airports, hospitals, and residential areas.

CONSTRUCTION

Unit includes die-cast metal housing, LED array, heat sinks, lens, foam gasket.

FINISH

White finish.

OPTICS

High quality PC lens. Efficiency LED array. Diffuse for uniform illumination.

ELECTRICAL

High efficiency integral 120V, 60Hz constant current dimming driver. Smooth flicker free deep dimming to 5%.

LISTINGS


ETL certification, IC rated. Suitable for wet location. 5 year warranty.




ORDERING INFORMATION

	-		-	
Series	Size	Lumen Package	CC	
DRF - (Ultra-Slim Flat Canless Downlight)	3 - (3")	05 - (500 lm, 8W)	5CC - 5 Color Changeable (2700K, 3000K, 3500K, 4000K, 5000K)	
	4 - (4")	06 - (650 lm, 10W)		
	6 - (6")	09 - (900 lm, 12W)		
	8 - (8")	15 - (1500 lm, 18W)		


DRF-305



DRF-406



DRF-609



DRF-815

